


Q50A

1000A RATIO CUSTOMISED AC CLAMP ON CT CURRENT TRANSFORMER

The model Q50A clamp on current transformer is designed for fast and easy measure the current in industrial and power environment, it has wide range of current measurement from 1mA to 1200A, high precision 0.1%, low phase shift, wide frequency from 10Hz to 200KHz, with harmonics measurement function, easy operation for measurement instruments. Meet EN61010-2-032 standard. Q50A current transformer clamp have many kinds of versions, for example 200A/300A/500A/1000A etc. The Q50A series AC clamp on cts are designed to extend the current measuring capabilities of DMMs, 4m banana or BNC, power instruments, oscilloscopes, hand-held scopes, recorders or loggers, clamp type grounding resistance tester, double clamp phase angle meter, energy meter calibrator and other diverse instruments.

Features

1. UL, CE CNAS mark;
2. High content permalloy core;
3. Holding wire diameter: $\phi 50\text{mm}$;
4. Conforms to EN 61010, 600V CAT III;
5. Frequency 10Hz-200kHz Bandwidth;
6. Low phase shift for power measurement;
7. Measurement range of 1mA to 1000A AC;
8. Industrial design & beautiful appearance;
9. High precision 0.1% for current measurement;
10. Improved ergonomic design & easy operation;
11. Designed for recorders, loggers, oscilloscopes, power and harmonic meters;



Application

1. Power meter;
2. Digital multi-meter;
3. Energy sub-meters;
4. Cable fault analysis;
5. Oscilloscopes meter;
6. Large industrial loads;
7. Power load monitoring;
8. Data logging/recording;
9. Power quality analyzer;
10. Power quality monitoring;
11. Phase volt-ampere meter;
12. Multi-function energy meter;
13. Earth resistance meter;
14. Power and harmonic meters;
15. CT secondary current detection;
16. Measuring around cable bundles;
17. Electric energy meter tester (on site);

Parameters

Electrical parameters

Ratio	1000: 1 or 2000:1 (customized)
Accuracy class	0.1%, 0.2%, 0.5%
Primary current	0 - 1000A AC
Secondary current	0-1A AC, 0 - 5A AC (customized)
Max. Cont. Input current	1200A
Load capacity	≤20Ω, standard 4Ω
Over voltage category	CAT III 600V
Output signal	500mA,1A,5A AC at nominal input current
Frequency range	10Hz-200kHz
Dielectric strength	3KV 50Hz/60Hz at 1 minute
Temperature range	-20°C to +55°C
Output	2.5 meter cable with D01 connector
Max. voltage not insulated conductors	720 V
Standard	EN 61010-1, EN 61010-2-032, EN 61010-2-031 IEC60044-1, & IEC61869-2, 600V CAT III
Installation	Clamp type
Output mode	Lead output (2.5m), 5m, 10m or customized
Connector	BNC, 4mm banana, signal cable(2 cores),customized

Accuracy (1000A Range)

0-10A	≤0.5%
10-100	≤0.2%
10-1000A	≤0.1%

Phase Shift(1000A Range)

0-10A	≤0.5°
10-100	≤0.2°
100-1000A	≤0.1°

Mechanical parameters

Dimensions (L x W x H) (mm)	102.9 x 219.6 x 28
Weight (g)	550
Holding wire diameter (mm)	φ50
Max. jaw opening (mm)	50
Jaw color	Blue or grey
Material	PC+ABS+Polycarbonate, UL94 V0

Selection guide

Model	Rate Current	Max Current	Secondary Current	Coil Ratio	Burden Resistance	Accuracy
Q50A5-200	200A	240A	5A	40:1	2.5VA	0.5%
Q50A5-300	300A	360A	5A	60:1	2.5VA	0.5%
Q50A5-400	400A	480A	5A	80:1	2.5VA	0.5%
Q50A5-500	500A	600A	5A	100:1	2.5VA	0.5%
Q50A5-600	600A	720A	5A	120:1	2.5VA	0.5%
Q50A5-800	800A	960A	5A	160:1	2.5VA	0.5%
Q50A5-1000	1000A	1200A	5A	200:1	2.5VA	0.5%
Q50A1-100	100A	120A	1A	100:1	customized	0.2%
Q50A1-200	200A	240A	1A	200:1	customized	0.2%
Q50A1-300	300A	360A	1A	300:1	customized	0.2%
Q50A1-400	400A	480A	1A	400:1	customized	0.2%
Q50A1-500	500A	600A	1A	500:1	customized	0.2%
Q50A1-600	600A	720A	1A	600:1	customized	0.2%
Q50A1-800	800A	960A	1A	800:1	customized	0.2%
Q50A1-1000	1000A	1000A	1A	1000:1	customized	0.1%
Q50A2-250	250A	300A	250mA	1000:1	customized	0.1%
Q50A2-300	300A	360A	300mA	1000:1	customized	0.1%
Q50A2-500	500A	600A	500mA	1000:1	customized	0.1%
Q50A2-1000	1000A	1000A	500mA	2000:1	customized	0.1%
Q50A3-500	500A	600A	200mA	2500:1	customized	0.1%
Q50A3-800	800A	960A	400mA	2000:1	customized	0.1%
Q50A3-1000	1000A	1000A	400mA	2500:1	customized	0.1%
Q50A4-500	500A	600A	250mA	2000:1	customized	0.1%
Q50A4-1000	1000A	1000A	250mA	4000:1	customized	0.1%
Q50A6-1000	1000A	1000A	200mA	5000:1	customized	0.1%